

SPECIFICATIONS 860 EURO

Lime cap.	8 mt
Fertilizer cap	6 mt
Voluminal cap.	191 ft ³ / 5,4 m ³
Overall length	191 in / 485 cm
Overall width	80 in / 203 cm
Curb weight	3960 lb / 1800 kg
P.T.O. standard	540 rpm
Minimum horsepower	100 hp
Number of disks	2
Conveyor width	16 in / 40.6 cm
Application width	Fertilizer: 39 to 134 ft (12 to 41 m) Lime: 30 to 40 ft (9 to 12 m)

Weigh- tronix Scale
Single axle : 3 load cells

TIRE SELECTION 860 EURO

Tires	Ply rating	Ground clearance	Overall height	Ground clearance	Overall height	Tire spacing
FARM UTILITY TIRES						
16.9 R 38	8	27.5 in (70 cm)	104 in (264 cm)	27.5 in (70 cm)	104 in (264 cm)	64 - 90 in (163 - 229 cm)

INNOTAG EURO SERIES LIME AND FERTILIZER SPREADERS 860 EURO



Innotag Distributions inc.
1-800-363-8727
www.innotag.com



EXPERTISE is the Solution

WITH THE ARRIVAL OF AN INCREASINGLY INTENSIVE AGRICULTURE, IT IS IMPORTANT TO HAVE THE RIGHT EQUIPMENT TO ACHIEVE HIGHER GOALS.



THE INNOTAG EURO SERIES SPREADERS

was designed for users interested in spreading fertilizer or lime with a simple, precise and versatile machine that will meet all their needs. Every component that comes in contact with the fertilizers is made of stainless steel for increased durability.



VARIABLE RATE CONTROLLER

Supplied as standard with the 860 Euro spreader, the console PS8000i offers many advantages:

- Manual application rate adjustment or automatic control.
- Traceability of applications by recording your sites either on a SD memory card or on the console's internal memory (up to 75 sites).
- "GPS" ready.



SULKY EUROPEAN FERTILIZER DISKS

High precision. Adjustable work width from 12 m (39 ft) to 41 m (134 ft). Tiered ejector blades. Clean border device. Manual ECOBORD or electric TRIBORD.



DISKS LIME

Disks are powered by a drive shaft and a gearbox lubricated with oil. Each disk is made of 4 paddles coated with a plastic material specifically designed to prevent lime accumulation on the paddles. You can reach 40 feet (12 m) in spread width for lime.



SUPPLY AND DOSAGE

A 16 in. (40 cm) chain conveyor allows for constant flow, paired with an adjustable door for precise dosage.

AVAILABLE OPTIONS



WEIGH-TRONIX SCALE

For higher precision, load cells can be installed on axles and on the tow bar. The weighing system offers a 99% precision rate.



PROTECTION CANVAS: Flip Top canvas

OTHER AVAILABLE OPTIONS:

- Traffic lights
- Independent braking system
- Wire steel screen