

SPECIFICATIONS	860 L
Lime cap.	8 mt
Voluminal cap.	191 ft ³ / 5,4 m ³
Overall length	191 in / 485 cm
Overall width	80 in / 203 cm
Curb weight	3960 lb / 1800 kg
P.T.O. standard	540 rpm
Minimum horsepower	80 hp
Number of disks	2
Conveyor width	16 in / 40.6 cm
Application width	30 ft. (10 m)

Weigh- tronix Scale
Tandem : 5 load cells
Single axle : 3 load cells

TIRE SELECTION 860 L

Tires	Ply rating	Ground clear- ance	Overall height	Tire spacing
FARM UTILITY TIRES				
12.5 L X 15	8	15 in 38 cm	85 in 216 cm	60 in (152 cm) 72 in (183 cm) 74 in (188cm)
16.5 L X 16.1	10	17.5 in 44.5 cm	88.5 in 225 cm	72 in (183 cm) 74 in (188 cm) 90 in (229 cm)
16.9 R 38	8	27.5 in 70 cm	104 in 264 cm	64 - 90 in (163 - 229 cm)
HIGHWAY SERVICE TIRES				
12.5 L X 15	12	15 in 38 cm	85 in 216 cm	60 in (152 cm) 72 in (183 cm) 74 in (188cm)
16.5 L X 16.1	10	17.5 in 44.5 cm	88.5 in 225 cm	72 in (183 cm) 74 in (188 cm) 90 in (229 cm)

Tandems can be raised by 8 inches as an option.

INNOTAG L SERIES LIME SPREADERS

860L



Innotag Distributions inc.
2080 Pierre-Louis-Le Tourneux,
Beloeil, Qc, J3G 6S8
Tel. : 450-464-7427
1-800-363-8727
Fax : 450-464-0874
www.innotag.com



EXPERTISE is the Solution

WITH THE ARRIVAL OF AN INCREASINGLY INTENSIVE AGRICULTURE, IT IS IMPORTANT TO HAVE THE RIGHT EQUIPMENT TO REACH HIGHER GOALS.



THE INNOTAG L SERIES SPREADERS

Designed for users interested in spreading with a simple, precise and versatile machine that will meet all their needs.



DISKS

Disks are powered by a drive shaft and a gearbox lubricated with oil. Each disk is made of 4 paddles coated with a plastic material specifically designed to prevent lime accumulation on the paddles. You can reach 30 feet (10 m) in spread width for lime.



SUPPLY AND DOSAGE

A 16 in. (40 cm) chain conveyor allows for constant flow, paired with an adjustable door for precise dosage.



OVERLAPPING WIDTH

Tandems can be adjusted to different widths for row cultivation.



LIME AND ASH

A direct P.T.O. drive allows lime and ash spreading. There are two speed ranges for better dosage control.

AVAILABLE OPTIONS




WEIGH-TRONIX SCALE

For higher precision, load cells can be installed on axles and on the tow bar. The weighing system offers a 99% precision rate.



PRECISION AGRICULTURE

The INNOTAG spreaders are compatible with the new fertilizer management technologies. Variable rates control can be added.



TIRES

You have a selection of industrial, commercial or high ground clearance tires. The ground clearance can reach 24 in (60 cm) clearance for spreading.

PROTECTION CANVAS: Flip Top canvas

Other available options:

- Traffic lights
- Independent braking system
- Wire steel screen
- Tandems can be raised up to 8 in